

View Online at <https://aerobasegroup.com/nsn/5985-00-301-3729>

**Unthreaded Mounting Hole Diameter:**

Between 0.135 inches and 0.141 inches

**Switch Type:**

Nontransfer

**Distance Between Mounting Facility Centers:**

1.680 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.75 single

**Insertion Loss In Decibels:**

2.00 single

**Connector End Design:**

Female

**Rf Power Handling Capability:**

0.2 watts average single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

Between 0.024 dc and 0.09 dc

**Actuator Voltage In Volts:**

12.0 and 5.0

**Switching Time:**

1.0 microseconds

**Switch Return Mechanism Type:**

Fail-safe

**Pole Quantity:**

1

**Throw Quantity:**

4

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Mounting Facility Pattern:**

Two position in-line single mounting facility pattern

**Terminal Type And Quantity:**

6 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A158a0