

View Online at <https://aerobasegroup.com/nsn/5985-00-304-8194>

**Frequency Rating:**

10.0 megahertz and 250.0 megahertz single frequency operating 10.0 megahertz and 250.0 megahertz single frequency crosstalk reference

**Unthreaded Mounting Hole Diameter:**

Between 0.154 inches and 0.161 inches

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

2.600 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

1.450 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.50 single

**Insertion Loss In Decibels:**

1.00 single

**Connector End Design:**

Female

**Rf Power Handling Capability:**

0.2 watts average single

**Minimum Crosstalk Rating In Decibels:**

60.0 single

**Actuator Current Type And Rating In Amps:**

Between 0.024 dc and 0.09 dc

**Actuator Voltage In Volts:**

12.0 and 5.0

**Switching Time:**

10.0 microseconds

**Pole Quantity:**

1

**Throw Quantity:**

4

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Terminal Type And Quantity:**

5 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A158a0