# NSN 5985-00-307-3385

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-307-3385

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2a first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.610 inches second flange and 3.640 inches second flange

Flange Depth:

0.923 inches first flange and 0.953 inches first flange

Flange Connecting Hole Diameter:

0.199 inches second flange all connection facilities and 0.203 inches second flange all connection facilities

**Voltage Standing Wave Ratio:** 

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

**Waveguide Outside Width:** 

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches first flange all connection facilities

**Waveguide Inside Width:** 

Between 1.867 inches and 1.877 inches

**Waveguide Inside Height:** 

Between 0.867 inches and 0.877 inches

**Waveguide Outside Height:** 

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

**Waveguide Length:** 

2.000 feet

Flexibility:

Flexible single tubing segment

# NSN 5985-00-307-3385

Waveguide Assembly - Page 2 of 2



М	ate	ria	۱.
IVI	ale	па	ı .

Copper alloy all tubing segment and flange

# **Surface Treatment:**

Any acceptable all tubing segment and flange outside surfaces

# **Style Designator:**

Straight type

# **Thread Series Designator:**

Unf first flange all connection facilities

# **Fsc Application Data:**

Antennas, waveguides, and related equipment

# Shelf Life:

N/a

# **Unit Of Measure:**

#### **Demilitarization:**

Yes - demil/mli

# Fiig:

A073a0