# NSN 5985-00-313-2436

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-313-2436

Application	Design:
-------------	---------

Transmission line

Body Style:

Coaxial type

**Overall Length:** 

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.812 inches

**Overall Height:** 

3.750 inches

Overall Width:

1.000 inches

Shaft Diameter:

### 0.250 inches

Shaft Length:

0.480 inches

**Unthreaded Mounting Hole Diameter:** 

0.140 inches

Voltage Standing Wave Ratio:

1.35

**Coaxial Connector Series Designation:** 

Ν

**Power Rating:** 

4.0 watts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

**Overall Attenuation Range In Decibels:** 

+0.0/+30.0

**Attenuation Variation Method:** 

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

**Frequency Range:** 

Between 400.000 megahertz and 5900.000 megahertz

## **Overall Attenuation Accuracy In Decibels:**

-0.25/+0.25

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Four position rectangular

## NSN 5985-00-313-2436

Variable Attenuator - Page 2 of 2



Shaft Type:

Round, slotted

#### Terminal Type And Quantity:

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

Fiig:

A223a0