## NSN 5985-00-313-2436

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-313-2436

| Application Design:   |
|---|
| Transmission line   |
| Body Style:   |
| Coaxial type  |
| Overall Length:   |
| 4.250 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.250 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.812 inches  |
| Overall Height:   |
| 3.750 inches  |
| Overall Width:  |
| 1.000 inches  |
| Shaft Diameter:   |
| 0.250 inches  |
| Shaft Length:   |
| 0.480 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.140 inches  |
| Voltage Standing Wave Ratio:  |
| 1.35  |
| Coaxial Connector Series Designation:                                     |
| N   |
| Power Rating:   |
| 4.0 watts average   |
| Insertion Loss At Minimum Attenuation In Maximum Decibels:                |
| 0.5   |
| Overall Attenuation Range In Decibels:                                    |
| +0.0/+30.0  |
| Attenuation Variation Method:   |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 4 unthreaded hole   |
| Frequency Range:  |
| Between 400.000 megahertz and 5900.000 megahertz                          |
| Overall Attenuation Accuracy In Decibels:                                 |
| -0.25/+0.25   |
| Adjustment Device Type And Quantity:                                      |
| 1 shaft   |
| Mounting Facility Pattern:  |

Four position rectangular

## NSN 5985-00-313-2436

Variable Attenuator - Page 2 of 2



Round, slotted

## **Terminal Type And Quantity:**

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

## Demilitarization:

Yes - demil/mli

Fiig:

A223a0