

View Online at <https://aerobasegroup.com/nsn/5985-00-313-2996>

**Application Design:**

Transmission line

**Body Material:**

Steel, qq-s-763, class 303, cond a

**Body Style:**

Round, terminal/terminals in opposite surface

**Terminal Material:**

Steel, stainless

**Terminal Surface Treatment:**

Gold plated

**Body Surface Treatment:**

Gold plated, mil-g-45204

**Overall Length:**

Between 1.130 inches and 1.170 inches

**Overall Diameter:**

0.380 inches

**Operating Temperature Range:**

-50.0/+125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

250.0 milliwatts average and 1.0 kilowatts peak

**Rf Signal Attenuation In Decibels:**

2.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.5 gigahertz

**Attenuation Accuracy In Decibels:**

-0.50/+0.50

**Unpackaged Unit Weight:**

10.0 grams

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 4.500 gigahertz

**Precious Material And Location:**

External surfaces gold

**Precious Material:**

Gold

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000