

View Online at <https://aerobasegroup.com/nsn/5985-00-316-6184>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

Round, terminal/terminals in opposite surface

**Overall Length:**

1.490 inches

**Overall Diameter:**

0.380 inches

**Voltage Standing Wave Ratio:**

1.35

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average and 200.0 watts peak

**Rf Signal Attenuation In Decibels:**

60.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+12.4 gigahertz

**Attenuation Accuracy Reference Frequency:**

12.4 gigahertz

**Attenuation Accuracy In Decibels:**

-1.20/+1.20

**Connection Type Per Function:**

Female input and male output

**Unpackaged Unit Weight:**

0.500 ounces

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 12.400 gigahertz

**Specification Data:**

26512-ga810ck manufacturers specification control

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A20000