

View Online at <https://aerobasegroup.com/nsn/5985-00-318-2538>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b all flanges all connection facilities

**Thread Direction:**

Right-hand all flanges all connection facilities

**Tubing Wall Construction Style:**

Convolute single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.2786 inches all flanges and 0.2814 inches all flanges

**Flange Inside Height:**

0.1386 inches all flanges and 0.1414 inches all flanges

**Flange Outside Width:**

0.735 inches all flanges and 0.765 inches all flanges

**Flange Outside Height:**

0.735 inches all flanges and 0.765 inches all flanges

**Flange Depth:**

0.195 inches all flanges and 0.225 inches all flanges

**Voltage Standing Wave Ratio:**

1.20

**Maximum Operating Pressure:**

60.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 0.358 inches and 0.362 inches

**Thread Size:**

0.112 inches all flanges all connection facilities

**Waveguide Inside Width:**

Between 0.2785 inches and 0.2815 inches

**Waveguide Inside Height:**

Between 0.1385 inches and 0.1415 inches

**Waveguide Outside Height:**

Between 0.218 inches and 0.222 inches

**Flange Connecting Facility And Quantity:**

4 threaded hole all flanges all connection facilities

**Flange Style:**

Choke type all flanges

**Waveguide Length:**

8.000 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber natural single tubing jacket

**Precious Material And Location:**

Tubing surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver single tubing segment all surfaces

**Style Designator:**

Straight type

**Thread Series Designator:**

Unc all flanges all connection facilities

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0