

View Online at <https://aerobasegroup.com/nsn/5985-00-320-4388>

Body Style:

Irregular

Overall Length:

1.670 inches

Overall Height:

0.710 inches

Overall Width:

1.340 inches

Frequency Rating:

0.0 gigahertz and 12.4 gigahertz single frequency voltage standing wave ratio

Unthreaded Mounting Hole Diameter:

0.120 inches

Switch Type:

Nontransfer

Distance Between Mounting Facility Centers:

0.440 inches single mounting facility pattern

Operating Temperature Range:

-55.0/+95.0 degrees celsius

Voltage Standing Wave Ratio:

1.50 single

Insertion Loss In Decibels:

0.30 single

Coaxial Connector Series Designation:

Sma

Connector End Design:

Female

Rf Power Handling Capability:

15.0 watts average single

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.12 dc

Actuator Voltage In Volts:

Between 20.0 and 30.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

20.0 milliseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

2

Rf Maximum Voltage Rating:

350.0 volts rms

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

2 unthreaded hole

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Material:

Metal body

Terminal Type And Quantity:

2 tab, solder lug and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0