

View Online at <https://aerobasegroup.com/nsn/5985-00-321-2146>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:**

2b first flange all connection facilities

**Thread Direction:**

Right-hand first flange all connection facilities

**Tubing Wall Construction Style:**

Corrugated single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.253 inches second flange and 1.256 inches second flange

**Flange Inside Height:**

0.628 inches second flange and 0.631 inches second flange

**Flange Outside Width:**

1.860 inches second flange and 1.890 inches second flange

**Flange Outside Height:**

1.860 inches second flange and 1.890 inches second flange

**Flange Inside Diameter:**

1.610 inches first flange and 1.640 inches first flange

**Flange Depth:**

0.610 inches first flange and 0.640 inches first flange

**Flange Connecting Hole Diameter:**

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Thready Qty Per Inch (tpi):**

32 first flange all connection facilities

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

**Thread Size:**

0.164 inches first flange all connection facilities

**Waveguide Inside Width:**

Between 1.118 inches and 1.126 inches

**Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

**Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

**Waveguide Longer Offset Distance:**

5.969 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole second flange all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Offset Distance:**

1.533 inches

**Special Features:**

Includes 0.375-24 unjf-3b boss pper ms33649-3

**Flexibility:**

Flexible single tubing segment

**Material:**

Copper alloy single tubing segment

**Surface Treatment:**

Enamel all tubing segment and flange outside surfaces

**Style Designator:**

Bend type

**Thread Series Designator:**

Unc first flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0