NSN 5985-00-321-2146

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-321-2146

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Inside Diameter:

1.610 inches first flange and 1.640 inches first flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange all connection facilities and 0.172 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

30.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Waveguide Longer Offset Distance:

5.969 inches

NSN 5985-00-321-2146

Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Offset Distance:

1.533 inches

Special Features:

Includes 0.375-24 unjf-3b boss pper ms33649-3

Flexibility:

Flexible single tubing segment

Material:

Copper alloy single tubing segment

Surface Treatment:

Enamel all tubing segment and flange outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0