

View Online at <https://aerobasegroup.com/nsn/5985-00-322-7793>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.10

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

**Waveguide Inside Width:**

Between 1.118 inches and 1.126 inches

**Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

**Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

**Waveguide Longer Offset Distance:**

5.062 inches

**Waveguide Offset Distance:**

3.562 inches

**Flexibility:**

Flexible single tubing segment

**Material:**

Aluminum all flange

**Precious Material And Location:**

Internal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver all tubing segment and flange inside surfaces

**Style Designator:**

Bend type

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0