

View Online at <https://aerobasegroup.com/nsn/5985-00-324-6402>

**Body Style:**

Irregular

**Overall Length:**

8.910 inches

**Overall Height:**

5.000 inches

**Overall Width:**

5.875 inches

**Frequency Rating:**

0.0 megahertz and 500.0 gigahertz single frequency operating  
0.0 megahertz and 500.0 gigahertz single frequency rf power handling  
0.0 megahertz and 500.0 gigahertz single frequency voltage standing wave ratio  
0.0 megahertz and 500.0 gigahertz single frequency insertion loss reference

**Unthreaded Mounting Hole Diameter:**

Between 0.189 inches and 0.199 inches

**Switch Type:**

Nontransfer

**Longest Horizontal Distance Between Mounting Centers:**

5.300 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

4.000 inches single mounting facility pattern

**Operating Temperature Range:**

+0.0/+55.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25 single

**Insertion Loss In Decibels:**

0.20 single

**Coaxial Connector Series Designation:**

Lc

**Connector End Design:**

Female

**Rf Power Handling Capability:**

15.0 kilowatts peak single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

1.5 dc

**Actuator Voltage In Volts:**

Between 18.0 and 30.0

**Switch Operation Sequence:**

Makes before breaks

**Switching Time:**

10.0 milliseconds

**Pole Quantity:**

1

**Throw Quantity:**

2

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Mounting Facility Pattern:**

Four position rectangular single mounting facility pattern

**Material:**

Aluminum body

**Surface Treatment:**

Enamel body outside surfaces

**Terminal Type And Quantity:**

1 connector, receptacle and 3 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A158a0