

View Online at <https://aerobasegroup.com/nsn/5985-00-324-6402>

Body Style:

Irregular

Overall Length:

8.910 inches

Overall Height:

5.000 inches

Overall Width:

5.875 inches

Frequency Rating:

0.0 megahertz and 500.0 gigahertz single frequency operating
0.0 megahertz and 500.0 gigahertz single frequency rf power handling
0.0 megahertz and 500.0 gigahertz single frequency voltage standing wave ratio
0.0 megahertz and 500.0 gigahertz single frequency insertion loss reference

Unthreaded Mounting Hole Diameter:

Between 0.189 inches and 0.199 inches

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

5.300 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

4.000 inches single mounting facility pattern

Operating Temperature Range:

+0.0/+55.0 degrees celsius

Voltage Standing Wave Ratio:

1.25 single

Insertion Loss In Decibels:

0.20 single

Coaxial Connector Series Designation:

Lc

Connector End Design:

Female

Rf Power Handling Capability:

15.0 kilowatts peak single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

1.5 dc

Actuator Voltage In Volts:

Between 18.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

10.0 milliseconds

Pole Quantity:

1

Throw Quantity:

2

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Aluminum body

Surface Treatment:

Enamel body outside surfaces

Terminal Type And Quantity:

1 connector, receptacle and 3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A158a0