## NSN 5985-00-324-7396

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-324-7396

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.870 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches
Overall Height:
1.969 inches
Overall Width:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Coaxial Connector Series Designation:
Bnc
Power Rating:
24.0 watts average
Overall Attenuation Range In Decibels:
+0.75/+8.00
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 220.000 megahertz and 400.000 megahertz
Adjustment Device Type And Quantity:
1 slotted screw
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, male and 2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

## NSN 5985-00-324-7396

Variable Attenuator - Page 2 of 2



Fiig:

A223a0