NSN 5985-00-324-7396

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-324-7396

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 5.125 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.870 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.625 inches |
| Overall Height: |
| 1.969 inches |
| Overall Width: |
| 1.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Coaxial Connector Series Designation: |
| Bnc |
| Power Rating: |
| 24.0 watts average |
| Overall Attenuation Range In Decibels: |
| +0.75/+8.00 |
| Attenuation Variation Method: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Frequency Range: |
| Between 220.000 megahertz and 400.000 megahertz |
| Adjustment Device Type And Quantity: |
| 1 slotted screw |
| Mounting Facility Pattern: |
| Four position rectangular |
| Impedance Rating In Ohms: |
| 50.0 input-output |
| Terminal Type And Quantity: |
| 2 connector, coaxial, male and 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

NSN 5985-00-324-7396

Variable Attenuator - Page 2 of 2



Fiig:

A223a0