NSN 5985-00-328-0616

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-328-0616

| Application Design: |
|--|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 5.900 inches |
| Overall Height: |
| 2.880 inches |
| Overall Width: |
| 5.550 inches |
| Operating Tempurature Range: |
| -5.0/+40.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.30 |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 2.0 watts peak |
| Mounting Facility Screw Thread Series Designator: |
| Unf |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.8 |
| Overall Attenuation Range In Decibels: |
| +0.0/+10.0 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 10 |
| Attenuation Per Step In Decibels: |
| 1.0 |
| Mounting Facility Type And Quantity: |
| 3 threaded hole |
| Mounting Thread Quantity: |
| 32 per inch |
| Adjustment Device Type And Quantity: |
| 1 knob |
| Mounting Facility Screw Thread Diameter: |
| 0.190 inches |
| Impedance Rating In Ohms: |
| 50.0 input-output |
| Terminal Type And Quantity: |

Terminal Type And Quantity

1 connector, coaxial, male and 1 connector, coaxial, female

NSN 5985-00-328-0616

Variable Attenuator - Page 2 of 2



| _ | | | | - | | |
|---|---|---|-----|---|------|--|
| C | h | 0 | Iŧ. | | ife: | |
| | | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0