## NSN 5985-00-328-1686

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-328-1686 **Body Style:** Rectangular **Overall Length:** 1.590 inches **Overall Height:** 1.550 inches **Overall Width:** 0.500 inches Frequency Rating: 0.0 gigahertz and 12.4 gigahertz single frequency operating 0.0 gigahertz and 12.4 gigahertz single frequency voltage standing wave ratio0.0 gigahertz and 12.4 gigahertz single frequency insertion loss reference0.0 gigahertz and 12.4 gigahertz single frequency crosstalk reference **Unthreaded Mounting Hole Diameter:** 0.135 inches Switch Type: Nontransfer **Distance Between Mounting Facility Centers:** 0.440 inches single mounting facility pattern **Operating Tempurature Range:** -55.0/+85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.40 single **Insertion Loss In Decibels:** 0.30 single **Coaxial Connector Series Designation:** Sm **Connector End Design:** Rf Power Handling Capability: 15.0 watts average single Minimum Crosstalk Rating In Decibels: 50.0 single **Actuator Operating Method:** Relay **Switch Operation Sequence:** Breaks before makes **Switching Time:** 20.0 milliseconds **Pole Quantity:** 

2

2

**Throw Quantity:** 

**Coupling Position Quantity:** 

## NSN 5985-00-328-1686

Radio Frequency Transmission Line Switch - Page 2 of 2



Mounting Facility Type And Quantity:
2 unthreaded hole
Mounting Facility Pattern:
Two position in-line single mounting facility pattern
Terminal Type And Quantity:
2 tab, solder lug and 3 receptacle, coaxial
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A158a0