NSN 5985-00-333-5948

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-333-5948

ew Online at https://aerobasegroup.com/nsn/5985-00-333-5948
oplication Design:
ansmission line
ody Style:
paxial type
verall Length:
063 inches
verall Height:
219 inches
verall Width:
375 inches
haft Diameter:
etween 0.247 inches and 0.250 inches
haft Length:
938 inches
stance Between Mounting Facility Centers:
125 inches
perating Tempurature Range:
0./+65.0 degrees celsius
oltage Standing Wave Ratio:
70
paxial Connector Series Designation:
ower Rating:
0.0 milliwatts peak
ounting Facility Screw Thread Series Designator:
IC
sertion Loss At Minimum Attenuation In Maximum Decibels
3
verall Attenuation Range In Decibels:
0.0/+60.0
tenuation Variation Method:
epped
ep Position Quantity:
tenuation Per Step In Decibels:
.0
ounting Facility Type And Quantity:
hreaded hole
equency Range:
tween 400.000 megahertz and 450.000 megahertz
verall Attenuation Accuracy In Decibels:
50/+0.50

NSN 5985-00-333-5948

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 shaft

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A223a0