NSN 5985-00-337-3718

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-337-3718 **Application Design:** Transmission line **Body Material:** Any acceptable **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Body Surface Treatment:** Any acceptable **Overall Length:** 3.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.750 inches Center To Center Distance Between Mounting Facilities Parallel To Width: 2.750 inches **Overall Height:** 0.370 inches **Overall Width:** 3.000 inches **Mounting Hole/stud Quantity: Body Length:** 3.000 inches **Unthreaded Mounting Hole Diameter:** Between 0.140 inches and 0.150 inches **Operating Tempurature Range:** -54.0 to 100.0 degrees celsius **Voltage Standing Wave Ratio:** 1.50 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms: Coaxial Connector Series Designation:** Sm Rf Signal Attenuation In Decibels: **Voltage Standing Wave Ratio Frequency Range:** +1.0 to 3.0 gigahertz **Attenuation Accuracy In Decibels:**

Not rated

Not rated

Frequency Sensitivity Attenuation In Decibels:

NSN 5985-00-337-3718

Fixed Attenuator - Page 2 of 2



Temperature Sensitivity Attenuation In Decibels:
Not rated
Connection Type Per Function:
Female input-output
Mounting Method:
Unthreaded hole
Terminal Type And Quantity:
5 connector
Frequency Range:
Between 1.000 gigahertz and 3.000 gigahertz
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A20000