## NSN 5985-00-339-8323



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-339-8323 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 3.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.840 inches **Overall Height:** 1.720 inches **Overall Width:** 0.500 inches **Unthreaded Mounting Hole Diameter:** 0.090 inches **Coaxial Connector Series Designation:** Osm **Power Rating:** 2.0 watts average **Overall Attenuation Range In Decibels:** +0.0/+30.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 unthreaded hole Frequency Range: Between 500.000 megahertz and 12.000 gigahertz **Adjustment Device Type And Quantity:** 1 knob **Mounting Facility Pattern:** Four position rectangular Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a

Demilitarization:

**Unit Of Measure:** 

Yes - demil/mli

## NSN 5985-00-339-8323

Variable Attenuator - Page 2 of 2



Fiig:

A223a0