## NSN 5985-00-341-5914

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-341-5914

## Application Design:

Transmission line

### **Body Material:**

Brass

#### Body Style:

Round, terminal/terminals in opposite surface

#### **Body Surface Treatment:**

Nickel plated

#### **Overall Length:**

2.468 inches

#### **Overall Diameter:**

0.827 inches

#### Voltage Standing Wave Ratio:

1.30

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Ν

#### **Power Rating:**

2.0 watts average and 2.0 kilowatts peak

#### **Rf Signal Attenuation In Decibels:**

30.0

#### Voltage Standing Wave Ratio Frequency Range:

+400.0/+450.0 megahertz

#### Attenuation Accuracy In Decibels:

-0.50/+0.50

#### **Connection Type Per Function:**

Female input and male output

#### **Mounting Method:**

Connector

#### **Terminal Type And Quantity:**

2 connector

#### Frequency Range:

Between 400.000 megahertz and 450.000 megahertz

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

# **NSN 5985-00-341-5914** Fixed Attenuator - Page 2 of 2

Fiig: A20000

