NSN 5985-00-357-9877

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-357-9877

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.190 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.800 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.800 inches
Overall Height:
3.000 inches
Overall Width:
5.000 inches
Scale Linearity:
Linear
Scale Division Quantity:
60
Operating Tempurature Range:
-28.0/+80.0 degrees celsius
Voltage Standing Wave Ratio:
2.10
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
6.0
Overall Attenuation Range In Decibels:
+20.0/+80.0
Attenuation Accuracy Reference Frequency:
1.0 gigahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.005 gigahertz and 1.055 gigahertz
Overall Attenuation Accuracy In Decibels:

-10.00/+10.00

NSN 5985-00-357-9877

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A223a0