

View Online at <https://aerobasegroup.com/nsn/5985-00-373-3368>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

7.313 inches

Overall Height:

3.547 inches

Overall Width:

3.000 inches

Frequency Rating:

0.0 gigahertz and 12.4 gigahertz single frequency voltage standing wave ratio

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

1.187 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.815 inches single mounting facility pattern

Operating Temperature Range:

-59.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.30 single

Insertion Loss In Decibels:

0.50 single

Coaxial Connector Series Designation:

N

Connector End Design:

Female

Minimum Crosstalk Rating In Decibels:

60.0 single

Actuator Operating Method:

Motor

Actuator Current Type And Rating In Amps:

3.0 dc

Actuator Voltage In Volts:

Between 18.0 and 30.0

Switch Operation Sequence:

Makes before breaks

Pole Quantity:

1

Throw Quantity:

4

Coupling Position Quantity:

4

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.190 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Steel body

Surface Treatment:

Paint body outside surfaces

Thread Series Designator:

Unf mounting facility hole

Terminal Type And Quantity:

1 connector, receptacle and 4 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0