NSN 5985-00-400-1468



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-00-400-1468 **Application Design:** Waveguide **Body Style:** Waveguide type **Overall Length:** 3.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.956 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.994 inches **Overall Height:** 3.484 inches **Overall Width:** 1.812 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches **Operating Tempurature Range:** -40.0/+55.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 **Power Rating:** 1.0 watts average **Waveguide Flange Type:** Cover **Waveguide Flange Designation:** Ug-419/u **Overall Attenuation Range In Decibels:** +0.0/+20.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 4 terminal w/mounting holes Frequency Range: Between 12.400 gigahertz and 18.000 gigahertz **Adjustment Device Type And Quantity:** 1 knob **Mounting Facility Pattern:** Four position rectangular **Terminal Type And Quantity:**

Shelf Life: N/a

2 flange

NSN 5985-00-400-1468

Variable Attenuator - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A223a0