NSN 5985-00-402-8013

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-402-8013

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.062 inches all flanges

Flange Inside Height:

0.505 inches all flanges

Flange Outside Width:

1.625 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Depth:

0.437 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches single flange single connection facility

Voltage Standing Wave Ratio:

1.15

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

120.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Waveguide Inside Height:

0.656 inches

Waveguide Longer Offset Distance:

3.310 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

Flange Style:

Cover type all flanges

Waveguide Offset Distance:

1.492 feet

Flexibility:

Flexible single tubing segment

Material:

Beryllium single tubing segment

Surface Treatment:

Any acceptable all flange outside surfaces

NSN 5985-00-402-8013

Waveguide Assembly - Page 2 of 2



Style Designator:

Bend type

Fsc Application Data:

Test station, guided missile remote control system

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0