

View Online at <https://aerobasegroup.com/nsn/5985-00-403-4136>

Application Design:

Transmission line

Body Material:

Aluminum

Body Style:

Round, terminal/terminals in opposite surface

Body Surface Treatment:

Anodized

Overall Length:

2.750 inches

Overall Diameter:

1.000 inches

Operating Temperature Range:

+0.0/+65.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 and 1.20

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

N

Power Rating:

2.0 watts average

Rf Signal Attenuation In Decibels:

6.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+6.0 gigahertz and +6.0/+12.4 gigahertz

Attenuation Accuracy Reference Frequency:

12.0 gigahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Connection Type Per Function:

Female input and male output

Unpackaged Unit Weight:

2.400 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000