NSN 5985-00-403-9716

Variable Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-00-403-9716



Application Design: Waveguide **Body Style:** Waveguide type **Overall Length:** Between 3.307 inches and 3.317 inches **Overall Height:** 2.440 inches **Overall Width:** 2.565 inches **Unthreaded Mounting Hole Diameter:** 0.116 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.50 **Power Rating:** 2.0 watts average and 7.0 kilowatts peak Insertion Loss At Minimum Attenuation In Maximum Decibels: 1.0 **Overall Attenuation Range In Decibels:** +0.0/+30.0 **Attenuation Variation Method:** Continuous Mounting Facility Type And Quantity: 4 terminal w/mounting holes **Frequency Range:** Between 32.900 gigahertz and 33.500 gigahertz **Adjustment Device Type And Quantity:** 1 electronic, current controlled **Mounting Facility Pattern:** Four position rectangular Impedance Rating In Ohms: 12.0 input **Terminal Type And Quantity:** 2 flange Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli

NSN 5985-00-403-9716

Variable Attenuator - Page 2 of 2

Fiig: A223a0

