

View Online at <https://aerobasegroup.com/nsn/5985-00-404-2286>

Body Style:

Rectangular

Overall Length:

3.250 inches

Overall Height:

3.000 inches

Frequency Rating:

0.0 megahertz and 50.0 megahertz single frequency operating0.0 megahertz and 50.0 megahertz single frequency rf power handling0.0 megahertz and 50.0 megahertz single frequency voltage standing wave ratio0.0 megahertz and 50.0 megahertz single frequency insertion loss reference0.0 megahertz and 50.0 megahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.169 inches

Switch Type:

Transfer

Voltage Standing Wave Ratio:

1.10 single

Insertion Loss In Decibels:

0.10 single

Coaxial Connector Series Designation:

C

Connector End Design:

Female

Rf Power Handling Capability:

1.5 kilowatts peak single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Relay

Switch Operation Sequence:

Makes before breaks

Rf Maximum Voltage Rating:

1.5 kilovolts peak

Coupling Position Quantity:

4

Mounting Facility Circle Radius:

1.312 inches single mounting facility pattern

Mounting Facility Type And Quantity:

3 unthreaded hole

Mounting Facility Pattern:

Six position circular single mounting facility pattern

Material:

Aluminum body

Precious Material And Location:

Connector surfaces rhodium and contact surfaces silver

Precious Material:

Rhodium and silver

Surface Treatment:

Enamel body outside surfaces

Terminal Type And Quantity:

4 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0