## NSN 5985-00-404-5221

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-404-5221

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.880 inches
Overall Height:
1.530 inches
Overall Width:
4.000 inches
Voltage Standing Wave Ratio:
1.00
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.0
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+20.0
+0.0/+20.0
+0.0/+20.0 Attenuation Variation Method:
+0.0/+20.0  Attenuation Variation Method:  Continuous
+0.0/+20.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:
+0.0/+20.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  4 threaded hole
+0.0/+20.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  4 threaded hole  Frequency Range:
+0.0/+20.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  4 threaded hole  Frequency Range:  Between 2.000 gigahertz and 12.400 gigahertz
+0.0/+20.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 4 threaded hole  Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz  Mounting Thread Quantity:
+0.0/+20.0  Attenuation Variation Method:  Continuous  Mounting Facility Type And Quantity:  4 threaded hole  Frequency Range:  Between 2.000 gigahertz and 12.400 gigahertz  Mounting Thread Quantity:  32 per inch
+0.0/+20.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 4 threaded hole  Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz  Mounting Thread Quantity: 32 per inch  Adjustment Device Type And Quantity:
+0.0/+20.0  Attenuation Variation Method: Continuous  Mounting Facility Type And Quantity: 4 threaded hole  Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz  Mounting Thread Quantity: 32 per inch  Adjustment Device Type And Quantity: 1 knob
Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 knob Mounting Facility Pattern:
Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 knob Mounting Facility Pattern: Four position rectangular

50.0 input-output

## NSN 5985-00-404-5221

Variable Attenuator - Page 2 of 2



## **Test Data Document:**

18323-990c929h02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

1	connector,	coaxial,	male and '	connector,	coaxial,	female
---	------------	----------	------------	------------	----------	--------

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0