NSN 5985-00-404-5221

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-404-5221

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

5.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.300 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.880 inches

Overall Height:

1.530 inches

Overall Width:

4.000 inches

Voltage Standing Wave Ratio:

1.00

Coaxial Connector Series Designation:

Ν

Power Rating:

10.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

1.0

Overall Attenuation Range In Decibels:

+0.0/+20.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 2.000 gigahertz and 12.400 gigahertz

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.190 inches

Impedance Rating In Ohms:

50.0 input-output

NSN 5985-00-404-5221

Variable Attenuator - Page 2 of 2



Test Data Document:

18323-990c929h02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0