NSN 5985-00-406-3964

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-406-3964 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Any acceptable **Overall Length:** 1.900 inches **Overall Diameter:** 0.750 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.34 and 1.50 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 1.0 watts average and 1.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 3.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+12.4 gigahertz and +12.4/+18.0 gigahertz **Attenuation Accuracy Reference Frequency:** 18.0 gigahertz **Attenuation Accuracy In Decibels:** -0.75/+0.75 **Connection Type Per Function:** Female input and male output **Unpackaged Unit Weight:** 2.200 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

NSN 5985-00-406-3964

Fixed Attenuator - Page 2 of 2



Fsc Application Data	a:
----------------------	----

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000