NSN 5985-00-406-3964

Fixed Attenuator - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5985-00-406-3964

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.900 inches
Overall Diameter:
0.750 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.34 and 1.50
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Ν
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.75/+0.75
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
2.200 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 18.000 gigahertz

NSN 5985-00-406-3964

Fixed Attenuator - Page 2 of 2



Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A20000