

View Online at <https://aerobasegroup.com/nsn/5985-00-406-6181>

Body Style:

Rectangular

Overall Length:

0.995 inches

Overall Height:

1.180 inches

Overall Width:

0.400 inches

Frequency Rating:

0.0 gigahertz and 1.0 gigahertz single frequency operating
0.0 gigahertz and 1.0 gigahertz single frequency rf power handling
0.0 gigahertz and 1.0 gigahertz single frequency voltage standing wave ratio
0.0 gigahertz and 1.0 gigahertz single frequency insertion loss
reference
0.0 gigahertz and 1.0 gigahertz single frequency crosstalk reference

Unthreaded Mounting Hole Diameter:

0.096 inches

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.125 inches single mounting facility pattern

Operating Temperature Range:

-65.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15 single

Insertion Loss In Decibels:

0.20 single

Rf Power Handling Capability:

25.0 watts average single

Minimum Crosstalk Rating In Decibels:

62.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

26.5

Switch Operation Sequence:

Makes before breaks

Switching Time:

6.0 milliseconds

Rf Maximum Voltage Rating:

750.0 volts rms

Coupling Position Quantity:

6

Mounting Facility Type And Quantity:

4 unthreaded hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Metal body

Surface Treatment:

Enamel body outside surfaces

Terminal Type And Quantity:

2 wire hook and 6 cable, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A158a0