# NSN 5985-00-407-2035

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-407-2035

## **Application Design:**

Transmission line

#### **Body Style:**

Cylindrical w/side terminals

### **Overall Length:**

2.234 inches

### **Overall Width:**

1.688 inches

#### First Flat Length:

0.344 inches

#### Flat Height:

0.218 inches

#### Body Diameter:

1.297 inches

#### Shaft Diameter:

## 0.249 inches

Bushing Length:

0.375 inches

### Shaft Length:

0.937 inches

### **Body Length:**

1.297 inches

## Operating Tempurature Range:

-55.0/+120.0 degrees celsius

#### **Power Rating:**

2.0 watts peak

## Mounting Facility Screw Thread Series Designator:

Unef

## Overall Attenuation Range In Decibels:

+0.0/+40.0

#### **Attenuation Variation Method:**

Continuous

## Mounting Facility Type And Quantity:

1 threaded bushing

## **Overall Attenuation Accuracy In Decibels:**

-2.00/+2.00

## Mounting Thread Quantity:

32 per inch

## Adjustment Device Type And Quantity:

2 shaft

## Shaft Type:

Round, flatted

## NSN 5985-00-407-2035

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.375 inches

## Impedance Rating In Ohms:

150.0 input and 1230.0 output

## Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

## Fiig:

A223a0