NSN 5985-00-409-7436

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-00-409-7436

Any acceptable
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
3.710 inches
Overall Diameter:
0.500 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.37
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Tnc
Power Rating:
2.0 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
40.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
Attenuation Accuracy Reference Frequency:
4.5 gigahertz
Attenuation Accuracy In Decibels:
-1.50/+1.50
Temperature Sensitivity Attenuation In Decibels:
0.00008
Connection Type Per Function:
Female output and male input
Unpackaged Unit Weight:
3.200 ounces
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector

NSN 5985-00-409-7436

Fixed Attenuator - Page 2 of 2



Frequency Range:
Between 0.000 gigahertz and 4.500 gigahertz
Precious Material And Location:
Body surfaces silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A20000