NSN 5985-00-411-3436

Waveguide Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5985-00-411-3436

2b flange connection facility hole **Body Style:** Rectangular **Overall Length:** 4.000 inches **Overall Height: 2.788** inches **Overall Width:** Between 1.865 inches and 1.885 inches Frequency Rating: 9.0 gigahertz and 9.6 gigahertz single frequency insertion loss reference Switch Type: Transfer **Longest Horizontal Distance Between Mounting Centers:** 1.280 inches single mounting facility pattern **Longest Vertical Distance Between Mounting Centers:** 1.220 inches single mounting facility pattern **Operating Tempurature Range:** -55.0/+100.0 degrees celsius **Voltage Standing Wave Ratio:** 1.08 single **Insertion Loss In Decibels:** 0.10 single **Maximum Operating Altitude Rating:** 50000.0 feet Rf Power Handling Capability: 125.0 watts average single Minimum Crosstalk Rating In Decibels: 50.0 single **Actuator Operating Method:** Relay **Switching Time:** 100.0 milliseconds Switch Return Mechanism Type: Fail-safe Waveguide Flange Type: Choke **Coupling Position Quantity: Mounting Facility Type And Quantity:**

4 threaded hole

NSN 5985-00-411-3436

Waveguide Switch - Page 2 of 2



т	h	re	ş	d	S	iz	e	•

0.164 inches flange connection facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Flange Connecting Facility And Quantity:

4 threaded hole

Material:

Aluminum alloy flang (s)

Thread Series Designator:

Unc flange connection facility hole

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0