NSN 5985-00-412-6152

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-412-6152

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
3.312 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.640 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.640 inches
Overall Height:
3.250 inches
Overall Width:
1.625 inches
Shaft Diameter:
0.451 inches
Shaft Length:
1.093 inches
Unthreaded Mounting Hole Diameter:
0.169 inches
Operating Tempurature Range:
-30.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Power Rating:
100.0 milliwatts peak
Waveguide Flange Type:
Choke
Waveguide Flange Designation:
Ug-136b/u
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 terminal w/mounting holes
Frequency Range:
Between 10.250 gigahertz and 10.500 gigahertz
Adjustment Device Type And Quantity:
1 shaft

NSN 5985-00-412-6152

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:

Four position rectangular

Shaft Type:

Round, slotted

Terminal Type And Quantity:

2 flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0