NSN 5985-00-412-9603

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-412-9603

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
3.000 inches
Overall Width:
2.688 inches
Body Diameter:
Between 2.250 inches and 2.312 inches
Shaft Diameter:
Between 0.249 inches and 0.251 inches
Shaft Length:
0.938 inches
Body Length:
2.062 inches
Schematic Diagram Designator:
" { "
Distance Between Mounting Facility Centers:
Between 1.485 inches and 1.515 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Power Rating:
600.0 milliwatts average and 2.5 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.0
Overall Attenuation Range In Decibels:
+10.0/+100.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 50.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-1.00/+1.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 shaft

NSN 5985-00-412-9603

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A223a0