## NSN 5985-00-415-4586

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-415-4586

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b all flanges all connection facilities

**Thread Direction:** 

Right-hand all flanges all connection facilities

**Bend Angle In Deg:** 

90.0 single bend h-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.896 inches all flanges and 0.904 inches all flanges

Flange Inside Height:

0.396 inches all flanges and 0.404 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.625 inches all flanges

Flange Inside Diameter:

1.406 inches all flanges and 1.437 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Thready Qty Per Inch (tpi):

32 all flanges all connection facilities

**Waveguide Outside Width:** 

Between 0.996 inches and 1.004 inches

**Thread Size:** 

0.164 inches all flanges all connection facilities

Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

**Waveguide Inside Height:** 

Between 0.396 inches and 0.404 inches

**Waveguide Outside Height:** 

Between 0.496 inches and 0.504 inches

**Waveguide Longer Offset Distance:** 

3.583 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

## **NSN 5985-00-415-4586** Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:
2.910 inches
Flexibility:
Rigid second tubing segment
Material:
Copper alloy first tubing segment
Surface Treatment:
Any acceptable all flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc all flanges all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0