## NSN 5985-00-415-6364

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-415-6364

Augliculus Decima
Application Design:
Waveguide
Body Style:
Irregular
Overall Length:
6.562 inches
Overall Height:
1.688 inches
Overall Width:
1.807 inches
End Application:
An/tpm-22
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
0.5 watts average and 1000.0 watts peak
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+82.5
Attenuation Variation Method:
Stepped
Step Position Quantity:
9
Attenuation Per Step In Decibels:
0.3
Frequency Range:
Between 0.000 megahertz and 1.000 megahertz
Overall Attenuation Accuracy In Decibels:
+0.50/+1.00
Adjustment Device Type And Quantity:
1 electronic, current controlled
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, male
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5985-00-415-6364

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0