NSN 5985-00-416-4822

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-416-4822

Application Design:
Transmission line
Body Material:
Brass, qq-b-626 or steel, corrosion resisting
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Gold plated or passivated
Overall Length:
1.430 inches
Overall Diameter:
0.420 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
250.0 milliwatts average and 100.0 watts peak
Rf Signal Attenuation In Decibels:
0.5
Attenuation Accuracy In Decibels:
-0.15/+0.15
Connection Type Per Function:
Female input and male output
Terminal Type And Quantity:
2 connector
Precious Material And Location:
Center conductor surface gold
Precious Material:
Gold
Fsc Application Data:
Communication equipment
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-00-416-4822

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000