

View Online at <https://aerobasegroup.com/nsn/5985-00-416-4825>

Application Design:

Transmission line

Body Material:

Brass or steel, qq-s-763, class 303

Body Style:

Round, terminal/terminals in opposite surface

Terminal Material:

Brass or steel, qq-s-763, class 303

Terminal Surface Treatment:

Gold plated or passivated, qq-p-35

Body Surface Treatment:

Gold plated or passivated, qq-p-35

Overall Length:

1.430 inches

Overall Diameter:

0.420 inches

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.30

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Sma

Power Rating:

250.0 milliwatts average and 100.0 watts peak

Rf Signal Attenuation In Decibels:

2.0

Voltage Standing Wave Ratio Frequency Range:

+2.0/+3.0 gigahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 2.000 gigahertz and 3.000 gigahertz

Precious Material And Location:

Center conductor surface gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000