NSN 5985-00-417-8287

Waveguide Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-417-8287

Cross Sectional Shape: Internal, rectangular external, rectangular Tubing Wall Construction Style: Seamless single tubing segment Flange Quantity: 2 Maximum Operating Pressure: 40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces Style Designator: Three bend type
Tubing Wall Construction Style: Seamless single tubing segment Flange Quantity: 2 Maximum Operating Pressure: 40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Seamless single tubing segment Flange Quantity: 2 Maximum Operating Pressure: 40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Flange Quantity: 2 Maximum Operating Pressure: 40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Maximum Operating Pressure: 40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Maximum Operating Pressure: 40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
40.0 pounds per square inch gage Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Special Features: Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Mounting bracket with two through holes provided and one bulkhead mounting bracket with four mounting holes Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Flexibility: Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Rigid single tubing segment Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Material: Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Aluminum alloy all tubing segment and flange Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Surface Treatment: Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
Chromate all tubing segment and flange outside surfaces and chromate zinc all tubing segment and flange outside surfaces and enamel tubing segment and flange outside surfaces Style Designator:
tubing segment and flange outside surfaces Style Designator:
Style Designator:
Three bend type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0