NSN 5985-00-418-3813

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-418-3813

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.590 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.562 inches
Overall Height:
2.590 inches
Overall Width:
3.380 inches
Shaft Diameter:
0.250 inches
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Bnc
Power Rating:
0.5 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.4
Overall Attenuation Range In Decibels:
+0.0/+102.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
102
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
3 threaded hole
Frequency Range:
Between 0.000 megahertz and 50.000 megahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
2 shaft

NSN 5985-00-418-3813

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern: Three position circular

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0