NSN 5985-00-419-5371

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-419-5371

3
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.640 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.562 inches
Overall Height:
3.812 inches
Overall Width:
1.953 inches
Coaxial Connector Series Designation:
Bnc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+100.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
3
Attenuation Per Step In Decibels:
1.0 and 10.0 and 25.0
Mounting Facility Type And Quantity:
3 unthreaded hole
Frequency Range:
Between 0.100 megahertz and 1.000 megahertz
Segment Attenuation Range In Decibels:
+0.00/+10.00 and +0.00/+40.00 and +0.00/+50.00
Segment Attenuation Accuracy In Decibels:
-0.125/+0.125 and -0.25/+0.25 and -0.25/+0.25
Adjustment Device Type And Quantity:
1 electronic, voltage controlled
Mounting Facility Pattern:
Three position circular
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:

3 connector, coaxial, female

NSN 5985-00-419-5371

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0