NSN 5985-00-420-0426

Fixed Attenuator - Page 1 of 2

Round, terminal/terminals in opposite surface

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:



View Online at https://aerobasegroup.com/nsn/5985-00-420-0426

Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Gold plated
Body Surface Treatment:
Gold plated
Overall Length:
1.220 inches
Overall Diameter:
0.340 inches
End Application:
Wsd: aircraft, prowler ea-6b
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
250.0 milliwatts average
Rf Signal Attenuation In Decibels:
25.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
20.0 grams
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.500 gigahertz

NSN 5985-00-420-0426 Fixed Attenuator - Page 2 of 2



Criticality Code Justification:
Feat
Special Features:
Weapon system essential; all metal surfaces may be passivated or gold plated
Precious Material And Location:
External surfaces gold
Precious Material:
Gold
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A20000