NSN 5985-00-420-0427

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-00-420-0427

Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Terminal Material:
Steel, stainless
Terminal Surface Treatment:
Gold plated
Body Surface Treatment:
Gold plated
Overall Length:
1.865 inches
Overall Diameter:
0.380 inches
Operating Tempurature Range:
-50.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Power Rating:
250.0 milliwatts average
Rf Signal Attenuation In Decibels:
40.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
Attenuation Accuracy In Decibels:
-1.50/+1.50
Connection Type Per Function:
Female input and male output
Unpackaged Unit Weight:
10.0 grams
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.500 gigahertz

NSN 5985-00-420-0427

Fixed Attenuator - Page 2 of 2



Special	Features:
---------	-----------

Metal surfaces may be passivated or gold plated

Precious Material And Location:

External surfaces gold

Precious Material:

Gold

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000