## NSN 5985-00-421-1262

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-421-1262

| Application Design:                           |
|---|
| Transmission line                             |
| Body Material:                                |
| Steel, corrosion resisting                    |
| Body Style:                                   |
| Round, terminal/terminals in opposite surface |
| Overall Length:                               |
| Between 1.205 inches and 1.215 inches         |
| Overall Diameter:                             |
| Between 0.370 inches and 0.380 inches         |
| Voltage Standing Wave Ratio:                  |
| 1.25  |
| Input Impedance Rating In Ohms:               |
| 50.0  |
| Output Impedance Rating In Ohms:              |
| 50.0  |
| Coaxial Connector Series Designation:         |
| Osm   |
| Power Rating:                                 |
| 1.0 watts average                             |
| Rf Signal Attenuation In Decibels:            |
| 6.0   |
| Voltage Standing Wave Ratio Frequency Range:  |
| +0.0/+4.0 gigahertz                           |
| Attenuation Accuracy In Decibels:             |
| -0.50/+0.50                                   |
| Unpackaged Unit Weight:                       |
| 0.260 ounces                                  |
| Terminal Type And Quantity:                   |
| 3 connector                                   |
| Frequency Range:                              |
| Between 0.000 hertz and 4.000 gigahertz       |
| Precious Material And Location:               |
| Contact surfaces gold                         |
| Precious Material:                            |
| Gold  |
| Fsc Application Data:                         |
| Antennas, waveguides, and related equipment   |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
|   |

--

## NSN 5985-00-421-1262

Fixed Attenuator - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A20000

