

View Online at <https://aerobasegroup.com/nsn/5985-00-421-2625>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Bend Angle In Deg:**

90.0 second bend h-plane

**Tubing Wall Construction Style:**

Seamless all tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.705 inches second flange and 0.707 inches second flange

**Flange Inside Height:**

0.394 inches second flange and 0.396 inches second flange

**Flange Outside Width:**

1.298 inches second flange and 1.328 inches second flange

**Flange Outside Height:**

1.298 inches second flange and 1.328 inches second flange

**Flange Inside Diameter:**

0.994 inches first flange

**Flange Depth:**

0.360 inches first flange and 0.390 inches first flange

**Flange Connecting Hole Diameter:**

0.144 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Waveguide Outside Width:**

Between 0.699 inches and 0.705 inches

**Waveguide Inside Width:**

Between 0.6195 inches and 0.6245 inches

**Waveguide Inside Height:**

Between 0.3085 inches and 0.3135 inches

**Waveguide Outside Height:**

Between 0.388 inches and 0.394 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges all connection facilities

**Flange Style:**

Cover type second flange

**Waveguide Length:**

7.875 inches

**Waveguide Center To Center Distance:**

4.187 inches

**Flexibility:**

Rigid fifth tubing segment

**Material:**

Rubber single tubing jacket

**Surface Treatment:**

Chromate third tubing segment outside surfaces

**Style Designator:**

Offset bend type

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A073a0